



## fi-7180 & fi-7280

Designed for heavy workloads and built to last, the Fujitsu fi-7180 and fi-7280 scanners offer exceptional return on investment (ROI) through increased scanning speeds and reduced operator intervention.

## **Scanning Performance**

With duplex scanning speeds of 160 images per minute at 300 dpi in Color, Grayscale, and Monochrome, the fi-7180 and fi-7280 protect your documents with acoustic sensors, ensure your data is captured with smart ultrasonic technology, and reduce rescans by cleaning up documents automatically in a single pass. Reliability is enhanced even further with new skew prevention technology for exceptional paper handling.

- Rapid power up time in less than 4 seconds.
- Hard and embossed credit card scanning up to 1.4mm thick
- · Scan sticky notes, taped receipts, and labels while securing against multifeeds
- Long document support up to 18.3 feet in PaperStream IP
- Latest USB 3.0 for forward compatibility
- 32/64 Bit Driver for PaperStream IP (TWAIN & ISIS)

## Fleet Management

Bundled with fi-7180 and fi-7280, the Scanner Central Admin provides IT departments an efficient way to manage medium to large scanner deployments. With remotely accessible fleet information, IT departments can now allocate resources effectively

based on scan volume, consumable wear, depreciation schedules and maintenance expiration.



Fujitsu fi-7180 and fi-7280 scanners have everything needed to integrate with thousands

of software applications in the market or with PaperStream Capture, an advanced yet easy to use scanning application provided in the box.

- · PaperStream IP Image Cleanup (TWAIN & ISIS)
- 2D Barcode Support
- PaperStream Capture batch scanning and PDF creation software
- · One-year Advance Exchange Limited Warranty

## **Accessories & Options**

The following options are available for purchase:

- Training & Installation to get the most out of the equipment
- Advanced Exchange Warranties in multi-year bundles
- ScanAid Kit with consumables and cleaning supplies
- fi-7180 Post-Imprinter for backside endorsing
- Black Background for fi-7280 flatbed auto-cropping
- · Carrier Sheet for double letter stitching

For full details on the Limited Warranty and other service programs, please go to www.lmagingService.com or call (800) 626-4686.













Technical Specifications

Color (24 bit)

Monochrome

Color 4,

ADF minimum

ADF maximum 6

Long document

Flatbed (fi-7280)

A8 sheets

fi-7180

fi-7280

fi-7180

fi-7280

fi-7180

fi-7280

fi-7180

fi-7280

Temperature

Relative humidity

Letter

Card 8

Grayscale 4,

Grayscale (8 bit)

Image Sensor Type

Optical Resolution

Output Color Depth

Internal Video Processing

Image Processing Function

Light Source

fi-7180 (ADF only) / fi-7280 (ADF+Flatbed)

Color: 24-bit; Grayscale: 8-bit; Monochrome: 1-bit

Multi-image, Blank page skip, i-DTC, Advanced-DTC Simplified-DTC, sRGB, Auto color, Deskew cropping, Punch hole removal, Tab cropping, Upper lower separation, Error diffusion, Dither, Moire removal, Image Emphasis, Color

Simplex: 80 ppm, Duplex: 160 ipm

Edge repair, Vertical Streaks Reduction

(200 dpi / 300 dpi)

1.7 seconds (200 dpi)

cleanup, Dropout color (None, Specified, Color Saturation),

Color CCDs (Color Charge Coupled Device)

White LFD Array

50 to 600 dpi, 1200 dpi 2

65536 levels (16-bit)

Hardware Deskew, cropping

600 dpi

Software

ADF

Flatbed (fi-7280)

2 x 2.13 in. (50.8 x 54 mm)

8.5 x 14 in. (216 x 355.6 mm)

8.5 x 11.69 in. (216 x 297 mm)

7.2 to 110 lb. (27 to 413 g/m²)

34 to 56 lb. (127 to 209 g/m²)

USB 3.0 (backward compatible)

100 to 240VAC ±10%

9.26 lb. (4.2 kg)

19.4 lb. (8.8 kg)

42° to 95° F (5° to 35° C)

Getting Started Guide

2D Barcode Support

PA03670-B005

PA03670-B505

20% to 80% (non-condensing)

Scanner Central Admin Agent

(32-bit/64-bit), Windows Server® 2012 (64-bit)

Up to 1.4 mm (portrait / landscape)

42 W or less (Sleep: 1.8 W; Standby: 0.35 W) 10

43 W or less (Sleep: 1.8 W; Standby: 0.35 W)

11.8 x 6.7 x 6.4 in. (300 x 170 x 163 mm)

11.8 x 22.7 x 9.2 in. (300 x 577 x 234 mm)

ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM,

PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error

Scan to Microsoft SharePoint<sup>13</sup>, ABBYY FineReader for ScanSnap,

Post-scan Imprinter (fi-7180 only), Carrier Sheet, Black Document Pad (fi-7280 only)

Windows® 8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows XP® (32-bit/64-bit), Windows Server® 2008

Ultrasonic Double Feed Detection Sensor Acoustic Paper Protection

Embossed Card Scanning Capability, Long Document Scanning, Scanner

Central Admin management, USB 3.0 Support, Acoustic Paper Protection, Automatic: Color Recognition, Paper-Size Detection, De-skew Correction,

One-year. Advance Exchange program also available; restrictions apply.

For full details, visit www.lmagingService.com or call (800) 626-4686

Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables:

ScanAid™ kit. For full details, visit www.lmagingService.com or call (800)

Sensor, Intelligent Multi-Feed Function (Manual Bypass)

Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series,

ENERGY STAR® / RoHS / EPEAT Silver

80 Sheets (Letter 20 lb. or A4: 80 g/m2)

8.5 x 220 in. (18.3') (210 x 5,588 mm) <sup>7</sup>

Models

Output

Resolution<sup>1</sup>

Performance

(A4, Portrait)

ADF Capacity

Document

ADF Feeding

Paper Weight

Physical Specifications

Environmental compatibility 12

Power requirements

Power consumption

(Thickness)

(Operating)

Dimensions (WxDxH) 11

Weight

Operating

Inbox Contents

Bundled Software

Options

OS Support

Other Features

Limited Warranty

Service Options

Part Number

Feed Detection Features


Interface

size

Scanning Speed







Fujitsu Computer Products of America, Inc. 1250 East Arques Avenue Sunnyvale, CA 94085-5401 Sales: (888) 425-8228, Tech Support: (800) 626-4686 • info@fcpa.fujitsu.com • http://us.fujitsu.com/fcpa





